









PCB LAYOUT



DIMENSION	TOLERANCE
BELOW 10 mm	± 0.25
10~50 mm	± 0.4
ABOVE 50 mm	± 0.7



LED CIRCUIT



SPECIFICATION :

- RATING : 12 VDC,50mA
- CONTACT RESISTANCE:100mΩ MAX(INITIAL)
- INSULATION RESISTANCE:100mΩ MIN
- BREAKDOWN VOLTAGE : 250 VAC FOR 1 MINUTE
- OPERATING FORCE : 250±50gf
- TOTAL TRAVEL : 0.4±0.15mm
- OPERATING TEMPERATURE: -20°C ~ 70°C
- LIFE CYCLE : 100,000 CYCLE

6	COVER	PC
5	TERMINAL	Bronze Silver Plated
4	CONTACT	SUS
3	LED	GaAsP/GaP
2	BUTTON	PA66
1	HOUSING	PA66
ITEM	PART NAME	MATERIAL

LED COLOR									
1	2	3	4	5	6	12	13	14	23
Red	Yellow	Green	Blue	White	Pure Green	Red Yellow	Red Green	Red Blue	Yellow Green

TOLERANCE				DRAWN		DATE		东莞德沃电子科技有限公司	
UNLESS OTHERWISE STATED				CHK'D		DATE		MODEL TS15-9W56WTX	
X.X	±0.25	∠	±0.5°	APPV'D		DATE		MATL	
X.XX	±0.1	UNIT	mm	SHEET		1 OF 1		FINISH	
REV	A	SCALE	4:1						
SIZE	A4	SHEET	1 OF 1						